

The logo for GMC Aircon features a stylized red swoosh above the text "gmc aircon" in a bold, black, sans-serif font.



Air Conditioner Collection

R410A








Pure Comfort



- SLEEP BUTTON:**
USED TO SET OR CANCEL SLEEP MODE ;
- FAN BUTTON:**
USED TO SELECT FAN SPEED IN SEQUENCE, HIGH, MEDIUM, OR LOW;
- TIMER BUTTON:**
USED TO SET OR CANCEL THE TIMER OPERATION;
- SWING BUTTON:**
USED TO STOP OR START VERTICAL ADJUSTMENT LOUVER SWINGING AND SET THE DESIRED AIRFLOW DIRECTION
- MODE BUTTON:**
PRESS THIS BUTTON TO SELECT THE OPERATION MODE ;
- ON/OFF BUTTON:**

FEATURE:

-  Quiet Operation
-  LED Display
-  Pre-Heat
-  Efficient Cooling & Heating
-  Timer Mode
-  Auto Restart
-  Emergency START/STOP
-  Dehumidification

R410A



ASW09

cooling:2600W
heating:2800W

ASW12

cooling:3500W
heating:3700W

ASW18

cooling:5200W
heating:5500W

ASW24

cooling:6500W
heating:6600W



ASW30

cooling:8800W
heating:9380W



Technical specification

Model No.			ASW09	ASW12	ASW18	ASW24	ASW30
TYPE			COOLING & HEATING	COOLING & HEATING	COOLING & HEATING	COOLING & HEATING	COOLING & HEATING
Cooling Capacity	W		2,600	3,500	5,200	6,500	8,800
Heating Capacity	W		2,800	3,700	5,500	6,600	9,380
Moisture removal	Liters/h		0.8	1.0	1.5	2.0	3.5
Indoor noise level at cooling	High	dB(A)	36	37	42	49	49
	Med.	dB(A)	33	34	39	44	47
	Low	dB(A)	29	32	36	40	45
Outdoor noise level	dB(A)		50	52	58	58	55
Electrical Data							
Power supply							
	V		198~264,50Hz,1P	198~264,50Hz,1P	198~264,50Hz,1P	198~264,50Hz,1P	198~264,50Hz,1P
Rated current	Cooling	A	4.2	5.6	9.1	10.2	13.8
	Heating	A	4.1	5.9	9	9.5	15.5
Rated input	Cooling	W	900	1200	2000	2238	3150
	Heating	W	880	1270	1970	2100	3400
Compressor	Type		Rotary	Rotary	Rotary	Rotary	Rotary
	LRA	A	21.5	34	42	60	90
Inner connecting cable	Core		4+Earth	4+Earth	4+Earth	5+Earth	5+Earth
R410A Defrost	Fuzzy		/	/	/	/	/
	Core		2	2	2	2	2
Fan System							
Indoor air circulation (Cooling/Heating)	m3/h		430/430	530/530	800/850	1100/1100	1250/1250
Connections							
Refrigerant	Gram		R410A	R410A	R410A	R410A	R410A
Connecting Pipe	Gas	mm	Φ9.52(3/8")	Φ9.523/8"	Φ12(1/2")	Φ15.88(5/8")	Φ15.88(5/8")
	Liquid	mm	Φ6(1/4")	Φ6(1/4")	Φ6(1/4")	Φ9.52(3/8")	Φ9.52(3/8")
MAX HEIGHT/LENGTH	M		5/10	5/10	5/15	5/15	5/15
Additional Refrigerant	R410A	+3M	20g	20g	/	/	/
		+4M	/	/	30g	30g	30g
Others							
Net dimensions (W x H x D)	Indoor	mm	718x240x180	770x240x180	900x280x202	900x280x202	1185x322x240
	Outdoor	mm	600x500x232	700x552x256	760x552x256	902x650x307	902x332x795
Net weight	Indoor	kg	7	8	11	14	19
	Outdoor	kg	25	30	36	52	65

- COOLING/HEATING Capacities are based on the following conditions:

COOLING		HEATING	
Indoor Temperature	27°C DB/19°C WB	Indoor Temperature	20°C DB
Outdoor Temperature	35°C DB/24°C WB	Outdoor Temperature	7°C DB/6°C WB

- Specifications and Design subject to change without notice